

# JALBUMPER SAS ESD JIJI174

# INDUSTRY<sub>4.0</sub>

\* Brevet International Déposé



**S3S SC CI LG FO SR**  
**EN ISO 20345:2022**  
**35 to 48**



Link-ESD

**0%  
METAL**



- Water-repellent full-grain leather
- PU/PU sole by BASF®
- ESD / Dissipative
- Polymer toe cap type B and midsole no metallic

- High-laced boot style outdoor incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. **Excellent impermeability**, no water crossing after 7h test. Very good breathability (evacuation of sweating well above normative requirements).
- The polyurethane toe cap, having been **SC-rated**, complies with **EN ISO 20345:2021**, which guarantees the footwear's sturdiness and longevity, as well as its increased resistance to impacts and scuffing.
- Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- TPU reinforcement for better protection of the malleoli.
- Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- Lace up with four pairs of no metallic eyelets and two pairs of **Quick Lio**. Laces 150 cm.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a **soft BASF®** **Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan insert** that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESD™ system**, an innovative multi-contact, static electricity dissipater.
- Ergonomic shoe, with broad synthetic polymer toe cap **Springtane-B™**. Impact resistance to 200 Joules. Minimum height after test  $\geq 4\text{mm}$  in relation to the Type A toe cap in accordance with Standard **22568-2:2019**.
- The **FlexTane™ S-type** mounting insole by Jallatte is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with standard **22568-4:2021**, antistatic, 100% composite, sewn directly onto the upper and covers 100% of the foot for all-round protection.
- Heel stiffener to reinforce the heel seat.
- Insole **PU / PU de BASF®**, design outdoor, excellent slip resistance.



## Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,35** ( $\geq 0,31$ )

B- Front to back **0,40** ( $\geq 0,36$ )

Additionnal requirement SR : Ceramic /Glycerin

C - Heel to the front **0,22** ( $\geq 0,19$ )

D- Front to back **0,27** ( $\geq 0,22$ )



- BExtremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.



www.jallatte.com

Weight	Gross weight (42) : g / Net weight (42) : g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	685 x 256 x 356